




# Cushion Rope


## Cushion Pac Ultra



DIAMETER		CONSTRUCTION	APPROX. WEIGHT		MINIMUM BREAKING LOAD	
inches	mm		lb/ft	kg/m	Tons	kN
1 1/2	38	8 x 31 Dy-Pac 8 CR/CC & CPU	4.5	6.7	110	981
1 5/8	41	8 x 31 Dy-Pac 8 CR/CC & CPU	5.3	7.9	128	1,141
1 3/4	44	8 x 31 Dy-Pac 8 CR/CC & CPU	6.2	9.2	150	1,336
1 7/8	48	8 x 31 Dy-Pac 8 CR/CC & CPU	7.1	10.5	171	1,522
2	51	8 x 31 Dy-Pac 8 CR/CC & CPU	7.9	11.7	192	1,708
2 1/8	54	8 x 31 Dy-Pac 8 CR/CC & CPU	9.1	13.5	220	1,962
2 1/4	57	8 x 31 Dy-Pac 8 CR/CC & CPU	10.1	15.1	245	2,181
2 3/8	60	8 x 31 Dy-Pac 8 CR/CC & CPU	11.2	16.7	271	2,410
2 1/2	64	8 x 31 Dy-Pac 8 CR/CC & CPU	12.6	18.7	304	2,706
2 5/8	67	8 x 31 Dy-Pac 8 CR/CC & CPU	14.0	20.8	339	3,018
2 3/4	70	8 x 36 Dy-Pac 8 CR/CC & CPU	15.2	22.6	351	3,120
2 7/8	73	8 x 36 Dy-Pac 8 CR/CC & CPU	16.6	24.7	400	3,562
3	76	8 x 36 Dy-Pac 8 CR/CC & CPU	18.1	26.9	436	3,881

# Cushion Pac Extreme

## (CPX)



DIAMETER		CONSTRUCTION	APPROX. WEIGHT		MINIMUM BREAKING LOAD	
inches			lb/ft	kg/m	Tons	kN
2 3/8		Cushion Pac Extreme	11.09	16.50	318	2829
2 1/2		Cushion Pac Extreme	12.27	18.25	350	3114
2 5/8		Cushion Pac Extreme	13.3	19.79	379	3372
2 3/4		Cushion Pac Extreme	14.49	21.56	398	2651
2 7/8		Cushion Pac Extreme	15.96	23.75	440	3914